

DEREE



Portable Air-control Tripod P-15 - SPECIFICATIONS

Load Capacity	15Kg (12Kg, 20Kg optional)
Weight	7.5Kg
Min. Height	770mm
Max. Height	1750mm
Ball Diameter	100mm
Air-control Working Distance	280mm



A100 - SPECIFICATIONS

Load capacity	15Kg
Head weight	3.5Kg
Pan range	360°
Tilt range	-85°/+85°
Counterbalance	3 setting + 0
Fluid drag	4 tilt / 4 pan
Temperature range:	-60°C/+60°C
Ball base diameter	100mm
Camera Mounting	Sliding quick release plate +/-45mm



B200 - SPECIFICATIONS

Load capacity	12Kg
Head weight	3Kg
Pan range	360°
Tilt range	-70°/+70°
Counterbalance	1 setting + 0
Fluid drag	2 tilt / 2 pan
Temperature range:	-60°C/+60°C
Ball base diameter	100mm
Camera Mounting	Sliding quick release plate +/-45mm



C300 - SPECIFICATIONS

Load capacity	12Kg
Head weight	3Kg
Pan range	360°
Tilt range	-85°/+85°
Counterbalance	1 setting + 0
Fluid drag	1
Temperature range	-60°C/+60°C
Ball base diameter	100mm
Camera Mounting	Sliding quick release plate +/-45mm



T-16C Carbon Fiber Tripod (2 stage) – SPECIFICATIONS <small>new</small>			
Bowl diameter	Ø 100mm	Tube diameter	Ø 16mm
Weight	2.8Kg	Load capacity	40Kg
Min. height	650mm	Max. height	1400mm
T-20C Carbon Fiber Tripod (2 stage) – SPECIFICATIONS <small>new</small>			
Bowl diameter	Ø 100mm	Tube diameter	Ø 20mm
Weight	3.5Kg	Load capacity	60Kg
Min. height	650mm	Max. height	1450mm



T-16 (2 stage) - SPECIFICATIONS			
Bowl diameter	Ø 100mm	Tube diameter	Ø 16mm
Weight	3.2Kg	Load capacity	40Kg
Min. height	650mm	Max. height	1400mm
T-20 (2 stage) - SPECIFICATIONS			
Bowl diameter	Ø 100mm	Tube diameter	Ø 20mm
Weight	4.8Kg	Load capacity	90Kg
Min. height	650mm	Max. height	1450mm



TS-16 (3 stage, spreader height adjustable) - SPECIFICATIONS

Bowl diameter	Ø 100mm	Tube diameter	Ø 16mm
Weight	3.3Kg	Load capacity	40Kg
Min. height	380mm	Max. height	1550mm



DL-10 - SPECIFICATIONS

Transport length	470mm
Build up radii	420mm
Weight	3.7Kg
Dolly diameter	Ø 100mm

DL-30 - SPECIFICATIONS

Transport length	630mm
Build up radii	460mm
Weight	4.5Kg
Dolly diameter	Ø 100mm



T-16 Mini - SPECIFICATIONS

Bowl diameter	Ø 100mm (Ø 150mm optional)	Tube diameter	Ø 16mm
Weight	2.6Kg	Load capacity	50Kg
Min. height	180mm	Max. height	750mm

T-20 Mini - SPECIFICATIONS

Bowl diameter	Ø 100mm	Tube diameter	Ø 20mm
Weight	3.5Kg	Load capacity	90Kg
Min. height	200mm	Max. height	700mm



Baby Tripod - SPECIFICATIONS

Bowl diameter	Ø 100mm (Ø 150mm optional)
Tube diameter	Ø 16mm
Weight	2.4Kg
Load capacity	50Kg
Min. height	100mm
Max. height	400mm



Accessories

Handle	Telescopic
	General
Adapter	For 75mm bowl head



S-10/S-15 DV Shoulder Bracket

- Fully Adjustable with Flexible Shoulder Pad
- Quick Release plate positioning is adjustable
- Two Release Levers adjust the unit up/down, and 'Swing' Arm(side/side) allows panning
- Folds to fit into Smaller DV Camera Bags
- Also available with GP-S/7.2 and NP-L168/7.2 for On-Board Battery Operation